













BÎO PDF



ES 65-L

Battery powered hydraulic cutting tool Ø 65 mm

Cuts copper and aluminium cables with light weight steel armoured (depending on cable type) Also suitable for fine stranded cable

Characteristics

- Open cutting head, rotatable
- Electronic control and monitoring of cutting operation
- One-button operating concept for controlling all tooling functions
- Ergonomic 2-component plastic housing with soft linings for comfortable and safe one hand operation
- Balanced centre of gravity for easy handling and effortless operations
- LED for workplace illumination
- High-performance 18V Lithium-ions batteries with high capacity and extremly short charging time
- High-performance motors for maximum operating speed
- 2-stage hydraulic system with fast feed and power
- Energy saving function by stopping motor after successful cutting operation
- Quick motor stop for high user safety
- Automatic retraction when cut is complete
- Manual retract in case of need
- Manual retract stop (MRS) for efficient operations
- Light diode for maintenance control, charge level indicator of the battery and for data transmission via USB-Adapter
- Environmentally-friendly hydraulic oil, quickly biodegradable

Article

| Afficie | | | |
|--|----------|--|--|
| Article | Part No. | | |
| Battery powered hydraulic cutting tool Ø 65 mm | ES65L | | |

Technical Data

| Tooliiiodi Bala | | | | |
|--------------------------------------|-------------------------|--|--|--|
| Battery voltage: | 18 V | | | |
| Battery capacity: | 3.0 Ah, Li-lon | | | |
| Charging time: | 22 min. | | | |
| Weight incl. battery: | 6.3 kg | | | |
| Ambient temperature: | -15° C up to +40° C | | | |
| Cutting range: | max. Ø 65 mm | | | |
| Number of cuts: | dependent on cable type | | | |
| Cutting force: | 40 kN | | | |
| Cutting time: | dependent on cable type | | | |
| Sound pressure level in 1 m distance | 70 dB (A) | | | |
| Vibrations | < 2.5 m/s ² | | | |

Accorcorios

| Accessories | | | | | |
|----------------|---|----------|--|--|--|
| | Description | Part No. | | | |
| 9 | USB adapter | PGA1 | | | |
| Q ₀ | 18 V Mains adapter for 115 V or 230 V voltage | NG2230 | | | |

Scope of supply

| ocope of supply | | | | | | |
|-----------------|--|----------|--|--|--|--|
| | Article | Part No. | | | | |
| | Battery 18 V / 3,0 Ah, Li-lon (54 Wh) | RAL2 | | | | |
| in the | Quick-charger for 18V Li-lon Batteries | LGL1 | | | | |